

	1	2	3	4	5	6	7																																																																																			
A								A																																																																																		
B	NOTES: Plunger: Brass, 20μ" MIN Au over, 50μ" MIN Ni over Barrel : Brass, 3μ" ,MIN Au over, 50μ" MIN Ni over Spring : Stainless Steel Mechanical Characteristics: Spring Force : 85g ± 20% at Working Length Mechanical Life : 1,000,000 cycle Electrical Characteristics: Current Rating : 2A Contact Resistance : 20 mΩ Max Operating Temperature range : -55~125° C Packing: PE Bag							B																																																																																		
C	Technical drawing of a plunger assembly. The drawing shows a side view of the plunger with a dashed centerline. Dimensions are provided for diameters and lengths. The diameters are: 1.829±0.051, 1.626±0.051, 1.499±0.051(2X), and 1.067±0.051. The lengths are: 0.406±0.152, 0.711±0.152, 6.629±0.152, 2.997MAX STROKE, and 1.499MID STROKE. A stroke diagram is also shown.							C																																																																																		
D								D																																																																																		
E								E																																																																																		
F								F																																																																																		
G	RoHS compliant Unit: mm <table><tr><td>Scale</td><td>Free</td><td></td><td></td><td></td><td></td><td>Date</td><td>Name</td><td colspan="2">Customer-No.</td></tr><tr><td colspan="2">TOLERANCE</td><td></td><td></td><td></td><td></td><td>Drawn</td><td>28.03.2018</td><td>Tom</td><td rowspan="3">ASSMANN WSW-No. A-CSL-S-020-B6</td></tr><tr><td>X.X</td><td>±0.20</td><td></td><td></td><td></td><td></td><td rowspan="2">Approved</td><td rowspan="2">28.03.2018</td><td rowspan="2">Winnie</td></tr><tr><td>X.XX</td><td>±0.10</td><td></td><td></td><td></td><td></td></tr><tr><td>X.XXX</td><td>±0.08</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>Drawing-No.</td></tr><tr><td>DIM</td><td>TOL</td><td></td><td></td><td></td><td></td><td colspan="3" rowspan="3"> ASSMANN WSW components </td><td>ASS 7957 CO</td><td>rev00</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td>Replace</td><td>Sheet</td></tr><tr><td>Angle</td><td>±3°</td><td>Ⓢ</td><td>Drawn</td><td>28.03.2018</td><td>Tom</td><td></td><td></td></tr><tr><td>Angle</td><td>TOL</td><td>Id.</td><td>Modification</td><td>Date</td><td>Name</td><td></td><td></td><td></td><td></td></tr></table>							Scale	Free					Date	Name	Customer-No.		TOLERANCE						Drawn	28.03.2018	Tom	ASSMANN WSW-No. A-CSL-S-020-B6	X.X	±0.20					Approved	28.03.2018	Winnie	X.XX	±0.10					X.XXX	±0.08								Drawing-No.	DIM	TOL					ASSMANN WSW components			ASS 7957 CO	rev00							Replace	Sheet	Angle	±3°	Ⓢ	Drawn	28.03.2018	Tom			Angle	TOL	Id.	Modification	Date	Name					G
Scale	Free					Date	Name	Customer-No.																																																																																		
TOLERANCE						Drawn	28.03.2018	Tom	ASSMANN WSW-No. A-CSL-S-020-B6																																																																																	
X.X	±0.20					Approved	28.03.2018	Winnie																																																																																		
X.XX	±0.10																																																																																									
X.XXX	±0.08								Drawing-No.																																																																																	
DIM	TOL					ASSMANN WSW components			ASS 7957 CO	rev00																																																																																
									Replace	Sheet																																																																																
Angle	±3°	Ⓢ	Drawn	28.03.2018	Tom																																																																																					
Angle	TOL	Id.	Modification	Date	Name																																																																																					
H								H																																																																																		
	1	2	3	4	5	6	7	SV4444																																																																																		