

# UCS SW 125-F 9005 - Side panel



2203365

<https://www.phoenixcontact.com/us/products/2203365>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Side panel for use with housing half shells 125 x 87 mm and 145 x 125 mm in size; panel thickness: 2 mm; total height of housing: 47 mm; material: polycarbonate; color: black similar to RAL 9005

## Your advantages

- High degree of application flexibility, thanks to the modular housing design
- Flexible PCB attachment, adapts to virtually all form factors
- Practical customization options
- Reduced logistics outlay, thanks to components which are compatible with one another

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 2203365       |
| Packing unit                         | 10 pc         |
| Minimum order quantity               | 20 pc         |
| Sales key                            | AC03          |
| Product key                          | ACFCAA        |
| GTIN                                 | 4055626427775 |
| Weight per piece (including packing) | 9.11 g        |
| Weight per piece (excluding packing) | 9.11 g        |
| Customs tariff number                | 84879090      |
| Country of origin                    | DE            |

# UCS SW 125-F 9005 - Side panel



2203365

<https://www.phoenixcontact.com/us/products/2203365>

## Technical data

### Notes

|               |                                                           |
|---------------|-----------------------------------------------------------|
| Assembly note | Please observe the application note in the download area. |
|---------------|-----------------------------------------------------------|

### Product properties

|                              |                    |
|------------------------------|--------------------|
| Product type                 | Housing side panel |
| Housing type                 | Universal housings |
| Housing series               | UCS                |
| Ventilation openings present | no                 |

### Dimensions

|        |         |
|--------|---------|
| Width  | 96 mm   |
| Height | 39.5 mm |
| Depth  | 2 mm    |

### Material specifications

|                                        |                  |
|----------------------------------------|------------------|
| Color (Housing)                        | black (RAL 9005) |
| Flammability rating according to UL 94 | V0               |
| CTI according to IEC 60112             | 225              |
| Insulating material                    | PC               |
| Housing material                       | PC               |
| Surface characteristics                | untreated        |

### Environmental and real-life conditions

#### Vibration test

|                        |                             |
|------------------------|-----------------------------|
| Specification          | IEC 60068-2-6:2007-12       |
| Frequency              | 10 - 150 - 10 Hz            |
| Sweep speed            | 1 octave/min                |
| Amplitude              | 0.15 mm (10 Hz ... 58.1 Hz) |
| Acceleration           | 2g (58.1 Hz ... 150 Hz)     |
| Test duration per axis | 2.5 h                       |
| Test directions        | X-, Y- and Z-axis           |

#### Glow-wire test

|                  |                        |
|------------------|------------------------|
| Specification    | IEC 60695-2-11:2014-02 |
| Temperature      | 850 °C                 |
| Time of exposure | 30 s                   |

#### Thermal stability / ball thrust test

|               |                        |
|---------------|------------------------|
| Specification | IEC 60695-10-2:2014-02 |
| Temperature   | 125 °C                 |
| Test duration | 1 h                    |
| Force         | 20 N                   |

# UCS SW 125-F 9005 - Side panel



2203365

<https://www.phoenixcontact.com/us/products/2203365>

## Mechanical strength / tumbling barrel

|                |                        |
|----------------|------------------------|
| Specification  | IEC 60068-2-31:2008-05 |
| Height of fall | 50 cm                  |
| Frequency      | 50                     |

## Shocks

|                                |                                   |
|--------------------------------|-----------------------------------|
| Specification                  | IEC 60068-2-27:2008-02            |
| Pulse shape                    | Half-sine                         |
| Acceleration                   | 15g                               |
| Shock duration                 | 11 ms                             |
| Number of shocks per direction | 3                                 |
| Test directions                | X-, Y- and Z-axis (pos. and neg.) |

## Test for substances that would hinder coating with paint or varnish

|               |                      |
|---------------|----------------------|
| Specification | VW PV 3.10.7:2005-02 |
| Result        | Test passed          |

## Degree of protection (IP code)

|                                       |                                                   |
|---------------------------------------|---------------------------------------------------|
| Specification                         | IEC 60529:1989-11 + AMD 1:1999-11 + AMD 2:2013-08 |
| Result, degree of protection, IP code | IP40                                              |

## Ambient conditions

|                                         |                                                    |
|-----------------------------------------|----------------------------------------------------|
| Max. IP code to attain                  | IP40                                               |
| Ambient temperature (operation)         | -40 °C ... 105 °C (depending on power dissipation) |
| Ambient temperature (storage/transport) | -40 °C ... 70 °C                                   |
| Ambient temperature (assembly)          | -5 °C ... 100 °C                                   |
| Relative humidity (storage/transport)   | 95 %                                               |

## Mounting

|               |      |
|---------------|------|
| Mounting type | Slot |
|---------------|------|

## Packaging specifications

|                   |        |
|-------------------|--------|
| Type of packaging | PE bag |
|-------------------|--------|

# UCS SW 125-F 9005 - Side panel



2203365

<https://www.phoenixcontact.com/us/products/2203365>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27190602 |
| ECLASS-15.0 | 27190602 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC002779 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 31261500 |
|-------------|----------|

# UCS SW 125-F 9005 - Side panel



2203365

<https://www.phoenixcontact.com/us/products/2203365>

## Environmental product compliance

|                                         |                                                              |
|-----------------------------------------|--------------------------------------------------------------|
| EU RoHS                                 |                                                              |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                                           |
| China RoHS                              |                                                              |
| Environment friendly use period (EFUP)  | EFUP-E                                                       |
|                                         | No hazardous substances above the limits                     |
| EU REACH SVHC                           |                                                              |
| REACH candidate substance (CAS No.)     | Perfluorobutane sulfonic acid (PFBS) and its salts(CAS: n/a) |
| SCIP                                    | 0e5bcbe5-56cd-4134-a006-8c58f2f9a75f                         |

Phoenix Contact 2025 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)