

PBCF4A100ALLB has not been replaced. Please contact your customer care center for more information.



⚠ Discontinued

Overview

|                      |                                                      |
|----------------------|------------------------------------------------------|
| Description          | Design busway runs for uniquely shaped data centers. |
| Model Name           | PB Busway Elbow Left, 100A                           |
| Includes             | Installation guide                                   |
| Standard Lead Time   | Usually Ships within 3 Weeks                         |
| Product Distribution | Canada , United States                               |

Output

|                                      |                     |
|--------------------------------------|---------------------|
| Nominal Output Voltage               | 208 3PH , , 600 3PH |
| Maximum Total Current Draw per Phase | 100 A               |

Input

|                       |                               |
|-----------------------|-------------------------------|
| Nominal Input Voltage | 208 3PH<br>415 3PH<br>600 3PH |
| Input Frequency       | 60 Hz                         |

Physical

|                 |          |
|-----------------|----------|
| Net Weight      | 5.82 kg  |
| Maximum Height  | 196.0 mm |
| Maximum Width   | 420.0 mm |
| Maximum Depth   | 420.0 mm |
| Shipping Weight | 9.09 kg  |
| Shipping Height | 422.0 mm |
| Shipping Width  | 548.0 mm |
| Shipping Depth  | 598.0 mm |
| Color           | Black    |

Environmental

|                             |               |
|-----------------------------|---------------|
| Operating Environment       | -10 - 40 °C   |
| Operating Relative Humidity | 0 - 95 %      |
| Operating Elevation         | 0-3000 meters |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                           |               |
|---------------------------|---------------|
| Storage Temperature       | -30 - 70 °C   |
| Storage Relative Humidity | 0 - 95 %      |
| Storage Elevation         | 0-4500 meters |

## Conformance

|                   |                              |
|-------------------|------------------------------|
| Approvals         | CSA , UL Listed , cUL Listed |
| Standard warranty | 1 year (parts only)          |

## Sustainable Offer Status

|       |                          |
|-------|--------------------------|
| RoHS  | Compliant                |
| REACH | REACH: Contains No SVHCs |