



Product: [70251PU](#) 

Sensor & Actuator, 4-Cond, Cu Section 0.14 mm², PUR

Product Description

PUR Sensor & Actuator Cable, 4 x 18 x 0.10 mm, 5 Million Continuous Flex Cycles, Trailing, Sunlight and Oil Resistant

Technical Specifications

Product Overview

Suitable Applications:	As a flexible, flame retardant and halogen-free control line in the industrial Mechanical- and Plant engineering, for high requirements, particularly for the employment in cable carriers (Drag chains) and moved machine parts.
------------------------	---

Physical Characteristics (Overall)

Conductor

Stranding	Material	No. of Conductors
18x38	BC - Bare Copper	4

Table Notes:	Extra fine-wired
Conductor Count:	4

Insulation

Material	Nominal Diameter
PP - Polypropylene	0.95 mm

Color Chart

Number	Color
Wire 1	Brown
Wire 2	White
Wire 3	Blue
Wire 4	Black

Outer Jacket

Material	Nominal Diameter	Diameter +/- Tolerance	Lab's Free	Oil Resistant
PUR - Polyurethane	3.5 mm	0.2 mm	Yes	Good

Electrical Characteristics

Min Insulation Resistance:	5000 MOhm*km
----------------------------	--------------

Voltage

Voltage Rating [V]	Voltage Test Dielectric
300 V	2.0 kV DC

Temperature Range

Operating Temp Range:	-50°C To +80°C
Operating Temp Range (Flexible Install):	-25°C To +80°C
Operating Temp Range (Drag Chain Op):	-25°C To +60°C

Mechanical Characteristics

Microbes and Hydrolyse Resistance:	Good
Min Bend Radius (W/o Pulling Strength):	35 mm
Min No. of Drag Chain Cycles:	2 Mio.
Drag Chain Parameters:	a = 5 m/s ² , horizontal 5 m, vertical 2 m,v = max. 200m/min.)

Standards

UL AWM Style Compliance:	AWM 20549
--------------------------	-----------

Applicable Environmental and Other Programs

Environmental Space:	Indoor/Outdoor
----------------------	----------------

Flammability, LS0H, Toxicity Testing

CSA Flammability:	CSA FT2
IEC Flammability:	IEC 60332-2-2
IEC 60754-1 - Halogen Amount:	Zero

Part Number

Variants

Item #	Color	Put-Up Type	Length	EAN
70251PU.00C100	Black	Coil	100 m	8719605012388
70251PU.00500	Black	Reel	500 m	8719605012371

History

Update and Revision:	Revision Number: 0.129 Revision Date: 09-10-2021
----------------------	--

© 2021 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.