



ATUM-19/4-0-STK Product Details

[Share](#) [Print](#) [Email](#)

ATUM-19/4-0-STK

Heat Shrink Tubing

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Heat Shrinkable Tubing
- Product Name = ATUM
- Product Source = U.K., U.S.
- Semiflexible
- Thin Wall Style

[View all Features](#)

TE Internal Number: 2341552001

Active

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

Quick Links

- Pricing & Availability
- Search for Tooling
- Product Feature Selector
- Contact Us About This Product

Documentation & Additional Information

Product Drawings:

- [Customer Drawing \(PDF, English\)](#)

Related Products:

- [Tooling](#)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Heat Shrinkable Tubing
- Color = Black

Environmental:

- Fluid Resistance = Moisture/Spray
- Operating Temperature (°C) = -55 - +110

Dimensions:

- Expanded ID, Min. (mm [in]) = 19.00 [0.748]
- Recovered ID, Max. (mm [in]) = 4.00 [0.157]
- Cut Length (mm [in]) = 1220.00 [48.031]

Conditions for Usage:

- Full Recovery Temperature (°C) = 110
- Shrink Temperature, Min. (°C) = 80
- High Temperature Compatible = No

Body Features:

- Product Name = ATUM
- Pliancy = Semiflexible
- Wall Style = Thin
- Wall Type = Dual
- Lining Type = Adhesive
- Material = Crosslinked Polyolefin
- Shrink Ratio = 3:1
- Fluid Type = Brake Fluid, Water
- Resistant To = Fluids, Mechanical Damage, Strain
- Wall Thickness - Full Recovery (Nominal) (mm [in]) = 2.25 [0.088]

Operation/Application:

- Application = Cable Jacket Repair Sleeve, Cable Jacketing, Insulation and Protection, Sealing
- Emission Free = No
- Product Use = Cable Breakouts, Cable Ends, Connector-to-Cable Transitions, Electronic Components, Harnesses, Wire Breakouts, Wire Splices

Housing Features:

- Material Systems = No

Packaging Features:

- Packaging Method = Stick

Industry Standards:

- Government/Industry Qualification = No
- Flammability Rating Type = Flame-Retardant
- UL Rating = None
- CSA Certified = No
- Approved Standards = None
- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Product Availability:

- Product Source = U.K., U.S.

Other:

- Brand = Raychem

Corporate Information

[About TE](#)
[Investors](#)
[News Room](#)
[Supplier Portal](#)
[Careers](#)
[Terms & Conditions](#)
[Privacy Policy](#)

Quick Links

[Distributor Inventory](#)
[Product Cross Reference](#)
[Documents & Drawings](#)
[Product Compliance Support Center](#)
[Site Map](#)

Customer Support

[Email or Chat With Us](#)
[Find a Phone Number](#)
[Knowledge Base](#)
[Manage Your Account](#)

Keep Me Informed

Receive TE News, Events & Technology Updates

 Enter your email address
