© 2017 TE Connectivity Ltd. family of companies. All Rights Reserved

CONNECTORS

MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES



✔ Active

TE CONNECTIVITY (TE)

HEADER HE13 STRAIGHT 3 P

AMPMODU | AMPMODU

281696-3
TE Internal Number: 281696-3

EU RoHS Compliant
EU ELV Compliant

Number of Positions 3

Centerline (Pitch) 2.54 mm [.1 in]

Connector & Contact Terminates To Printed Circuit Board

Connector Style Plug

Header Type Shrouded

PRODUCT DRAWING
English

3D PDF

DOCUMENTATION

Product Drawings

HEADERS HE13, SINGLE ROW, STRAIGHT
PDF
English

CAD Files

Customer View Model
2D_DXF.ZIP
English

Customer View Model
3D_IGS.ZIP
English

Downloaded from Arrow.com.

3D PDF

PDF

English

Customer View Model

3D_STP.ZIP

English

Customer View Model

3D_STP.ZIP

English

Customer View Model

2D_DXF.ZIP

English

3D PDF

PDF

3D

Customer View Model

3D_IGS.ZIP

English

Product Specifications

Product Specification

MODULAR HEADERS AND PLUGS ACCORDING TO IEC 60603-8 SERIES (HE13 HE14 SERIES)

PDF

French

Product Environmental Compliance

TE Material Declaration

MD_281696-3_06232014634_dmtec

PDF

English

FEATURES

Please review product documents or contact us for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

Connector & Contact Terminates To Printed Circuit Board
Connector Style Plug
Header Type Shrouded
PCB Mounting Orientation Vertical
Connector Type Header
Row-to-Row Spacing 2.54 mm [.1 in]
Gasket Without
Product Type Connector
Stabilizers Without
Board Standoff Without
Strain Relief Without

Downloaded from Arrow.com.

Configuration Features

Selectively Loaded No
Number of Positions 3
Number of Rows 1
Keyed No

Body Features

Post Size .64 mm [.025 in]

Contact Features

Solder Tail Contact Plating Material Tin-Lead
Contact Protection With
Contact Shape Square
Contact Current Rating (Max) (A) 3
Contact Base Material Phosphor Bronze
Contact Type Pin
Contact Mating Area Plating Material Gold
Contact Protection Type Shrouded

Termination Features

Termination Method to PC Board Through Hole
Termination Method to Wire/Cable Crimp, Insulation Displacement Crimp (IDC)
Termination End Plating Material Tin-Lead
Termination Post Length (mm) 2.9

Mechanical Attachment

Panel Mount Retention Without
Mating Connector Lock Without
PCB Mounting Style Through Hole
Mating Alignment Type Polarization
PCB Mount Retention Without
Mating Alignment Without

Housing Features

Centerline (Pitch) 2.54 mm [.1 in]
Housing Style 2-Sided
Housing Material High Temperature Thermoplastic
Housing Color Blue

Dimensions

Shrouded End Dimension (mm) 1.27
Mating Post Length (mm) 6.75

Usage Conditions

Operating Temperature Range (°C) -55 – 105

Industry Standards

Approved Standards CSA LR7189, UL E28476
UL Flammability Rating UL 94V-0

Downloaded from Arrow.com.

Packaging Features

Packaging Quantity 500
Packaging Method Box

PRODUCT COMPLIANCE

Statement of Compliance

Statement of Compliance
PDF

Downloaded from Arrow.com.