

Part Number : 2147572021

Product Description : Micro-Fit 3.0 Male-to-Micro-Fit 3.0 Male Off-the-Shelf (OTS) Cable Assembly, Dual Row, 150.00mm Length, Gold (Au) Plating, 2 Circuits,

Black

Series Number: 214757

Status: Active

Product Category: Power and Signal Cable

Assemblies



Documents & Resources

Drawings

2147572021 sd.pdf

3D Models and Design Files

STEP AP242

SOLIDWORKS

Creo

Product Environment Compliance

Compliance

| GADSL/IMDS | Not Relevant |
|--------------------|---|
| China RoHS | ⊚ per SJ/T 11365-2006 |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Not Contained per D(2024)7663-DC (21 Jan 2025) |
| EU RoHS | Compliant per EU 2015/863 |

Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

Industry Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest

PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

Part Details

General

| Status | Active |
|------------------------|--|
| Category | Power and Signal Cable Assemblies |
| Series | 214757 |
| Description | Micro-Fit 3.0 Male-to-Micro-Fit 3.0 Male Off-the-Shelf (OTS) Cable Assembly, Dual Row, 150.00mm Length, Gold (Au) Plating, 2 Circuits, Black |
| Application | Power, Wire-to-Wire |
| Assembly Configuration | Dual Ended Connectors |
| Connector to Connector | Micro-Fit 3.0 Both Ends |
| Product Name | Micro-Fit 3.0 |
| Туре | Discrete Wire Assembly |
| UPC | 193264501786 |

Electrical

| Current - Maximum per Contact | 8.5A |
|-------------------------------|------------|
| Voltage - Maximum | 300V AC/DC |

Physical

| Cable Length | 150.00mm |
|--------------------|----------|
| Circuits (Loaded) | 2 |
| Circuits (maximum) | 2 |
| Color - Resin | Black |

| Gender | Male-Male |
|--------------------------------|----------------------|
| Lock to Mating Part | Yes |
| Material - Metal | Phosphor Bronze |
| Material - Plating Mating | Gold |
| Material - Plating Termination | Tin |
| Material - Resin | Nylon |
| Net Weight | 4.540/g |
| Number of Rows | 2 |
| Overmolded | No |
| Packaging Type | Bag |
| Pitch - Mating Interface | 3.00mm |
| Plating min - Mating | 0.762μm |
| Plating min - Termination | 2.540µm |
| Single Ended | No |
| Termination Interface Style | Crimp or Compression |
| Wire/Cable Type | UL 1061 |
| Wire Size (AWG) | 18 |

Mates With / Use With

Mates with Part(s)

| Description | Part Number |
|---|--------------|
| Micro-Fit 3.0 Dual Row Receptacle Housings | <u>43025</u> |

This document was generated on Oct 13, 2025