MINI® FL1 SERIES 32V PCB FUSE HOLDER



Specifications

Current Rating Continuous:22 AmpsCurrent Rating Max:30 AmpsFuse Type:MINIFlammability Rating:UL 94 V-0Input Terminals:MINI Fuse BladesMounting Method:PCB MountMax Voltage Rating:32 VDC

Applications

- Automotive PCB Fusing
- Accessory, Sensor, or Vehicle Control Circuit Protection

Features And Benefits

- Compatible with MINI® blade fuses up to 30 amps (sold separately)
- Made for installing a MINI® blade fuse on a printed circuit board (PCB)
- Multiple MINI® FL1 Series fuse holders can be mounted in a row
- Heat-resistant, black, glass-fiber-reinforced PBT body with a UL 94 V-0 flammability rating is ideal for automotive applications
- Tin-plated copper alloy terminals fit into a 7.62mm pitch

Description

The MINI® FL1 Series 32V PCB Fuse Holder makes it simple to add a single MINI® blade fuse up to 30 amps (sold separately) to a printed circuit board (PCB). If you need circuit protection for multiple circuits, nearly any number of MINI® FL1 Series fuse holders can be mounted in a row.

As a MINI® fuse holder for PCB applications, it features a heat-resistant, black, thermoplastic body with a UL 94 V-0 flammability rating. This makes it ideal for holding an automotive fuse that protects accessory, sensor, and vehicle control circuits. Its tin-plated copper alloy fuse holder terminals fit into a 7.62mm pitch.

Web Resources

Download 2D print, installation guide and technical resources at: **littelfuse.com/MINIFL1**

Ordering Information

PART NUMBER	DESCRIPTION	CURRENT RATING MAX	FUSE TYPE	MOUNTING METHOD	MAX VOLTAGE RATING
178.6764.0001	Holder For FL1 (MINI) PCB 100 PC	30 Amps	MINI	PCB Mount	32 VDC

